

Esmeril Recto GGS 30 LPS

SKU	0601.2B5.2E0-000
EAN	4053423319910



Alcance de la entrega

1 x wrench (1 619 P21 169)	✓
Collet 1/4" with nut (1 619 P21 254)	✓

Datos técnicos

Potencia útil	400,0
Peso	1,800
Velocidad en vacío	7,000 – 33,000 rpm
Velocidad de giro en vacío, hasta	33.000,0
Velocidad de giro en vacío, desde	7.000,0
Max. polishing tool diameter	50,0
Ø máx. de muela abrasiva	25,0
Ø máx. de pinza de sujeción	8 mm 6 mm 3 mm 1/4"
Potencia absorbida	750,0
Interruptor	PROtection Switch
Cara del husillo amolador	15,0
Cara de la tuerca tensora	17,0
Ø del cuello del husillo	43,0
Información adicional versión corta	The GGS 30 LPS straight grinder offers a single-wrench spindle lock function, a protection switch, and speed control
Tolerancia K	3,0
Nivel de presión acústica	80,0
Nivel de ruido	The A-rated noise level of the power tool is typically as follows: Sound pressure level 80 dB(A); Sound power level 91 dB(A). Uncertainty K= 3 dB.
Nivel de potencia acústica	91,0
Quantity per pallet	84
Peso neto	2,550 kg
Peso bruto	2,550 kg

País de origen	China
----------------	-------



Beneficios del producto

- Designed for use protection with PROtection switch, kickback control, soft start, and restart protection
- Easy and convenient - change accessories with only one wrench
- Fast and efficient thanks to the powerful 750 W motor